

ZRA 1212 B1

ZRA
Standard swivel joints

JCQ
Flat fan nozzle



STANDARD SWIVEL JOINTS

ZRA/ZRB/ZRC are standard swivel joints for manufacturing plants requiring product diversification. The fitting and adjustment of the joints can be done easily by tightening the hexagonal screw cap.

- Typical applications
 - Cleaning equipment used in pre-treatment for coating process.
 - Continuous casting cooling.
- Inlet thread size 1/8", 1/4", 3/8", 1/2", 3/4"
- Outlet thread size 1/8", 1/4", 3/8", 1/2", 3/4"
- Max working pressure **LP** 21 bar
- Materials
 - B1** AISI 303 Stainless steel
 - B31** AISI 316L Stainless steel
 - T1** Brass

Code	RG poll	RF poll	L mm	A deg	WS mm	W g
ZRA 1212 xx YY	1/8"	1/8"	38	50°	22	57
ZRA 2525 xx YY	1/4"	1/4"	57			75
ZRA 2626 xx YY	1/4"	1/4"	67	60°	27	147
ZRA 3826 xx YY	3/8"	1/4"	67			150
ZRA 3838 xx YY	3/8"	3/8"	70			155
ZRA 5050 xx YY	1/2"	1/2"	74	40°	27	186
ZRA 7575 xx YY	3/4"	3/4"	92		40	468

HOW TO MAKE UP THE PRODUCT CODE EX.: ZRA 1212 B1SB

ZRA 1212 xx YY

CONNECTION

- SB - BSP
- SN - NPT

MATERIAL


- B1 - AISI 303 Stainless steel
- B31 - AISI 316L Stainless steel
- T1 - Brass

OUTLET THREAD SIZE


- 12 - 1/8"

INLET THREAD SIZE


- 25 - 1/4"
- 38 - 3/8"
- 50 - 1/2"
- 75 - 3/4"



ZRA



ZRB



ZRC

Nozzle type	Inlet	Outlet
ZRA	Male	Female
ZRB	Female	Female
ZRC	Welded	Female